

4PMB

Four-Post MKS Lift for Mercedes-Benz vehicles

**WIDEST
RUNWAYS!**



*Shown with optional swing air jacks
and optional AlignLights.*

- ✓ **The only Mercedes-Benz approved alignment rack for Sprinter**
- ✓ **26 in. (660 mm) runway width**
- ✓ **18,000-lb. (8165 kg) capacity**
- ✓ **Patented features maximize productivity**

Specifications

Max. vehicle weight	18,000 lbs. (8164 kg)
Max. wheelbase	
General service	193 in. (4902 mm)
Two-wheel alignment*	177 in. (4496 mm)
Four-wheel alignment	177 in. (4496 mm)
Min. four-wheel alignment	88 in. (2235 mm)
Max. lifting height	75 in. (1905 mm)
Alignment height	Any of 16 lock positions
Minimum height	8.75 in. (222 mm)
Overall height	98 in. (2489 mm)
Tread width	
Min. inside	40 in. (1016 mm)
Max. outside	92 in. (2337 mm)
Motor	3 hp, 208-230 VAC, 60 Hz, 1 ph
Air	90-150 psi (6.2-10.3 bar)**

* Long wheelbase vehicles may require jacking compensation
 ** 125 psi (8.6 bar) required for full jack capacity

Models

4PMBE	MKS 4-Post
4PMB-PSE	MKS 4-Post with and PowerSlide® slippates
4PMB-ISE	MKS 4-Post with FIA, Inflation Station, and PowerSlide®

Options

20-2336-1	Low-friction PowerSlide® turnplates
20-2113-1	Low friction 50 mm turnplates (non-PowerSlide®)
20-2993-1	AlignLights system
20-3146-1C	40-in. ramp extension kit (26-in. wide) for extremely low clearance vehicles or high floor slope situation Specify Mercedes-Benz black when ordering.
133-84-1	9,000-lb. (3175 kg) capacity Swing Air Jack

4PMB-PSE

PowerSlide® Locking System

PowerSlide® control

Push-button locks or unlocks the slippates and turnplates.



PATENTED



PowerSlide® turnplates

Save time by eliminating struggle with turnplate pins.

4PMB-ISE

FIA with Inflation Station and PowerSlide®



FIA console

Controls PowerSlide® and Inflation Station features.

Integrated inflation reels

Automatically fills or bleeds each tire.





Because of continuing technological advances, specifications, models and options are subject to change without notice.

PowerSlide and HawkEye are registered trademarks of Hunter Engineering Company.

0617DH

Copyright © 2017, Hunter Engineering Company

4PMB plan view



HUNTER

Engineering Company

www.hunter.com

Form 6129-T, 06/17
 Supersedes form 6129-T, 05/16