

# **VAS 741 075 Tire Changer**

*Powerful and operator-friendly*

**NEW**



# Specifications

<b>Power requirements</b>	230V, 1ph, 50/60HZ
<b>Air supply requirements</b>	8-12 bar (115-175 psi)
<b>Mount / demount tool</b>	Leverless head
<b>Clamping type</b>	Center with Quick Clamp
<b>Bead loosening type</b>	Upper / lower roller
<b>Match-mounting capable</b>	Yes
<b>Rim diameter range</b>	12-30 in. (305-762 mm)
<b>Maximum...</b>	
Tire diameter	45 in. (1143 mm)
Wheel width	15 in. (381 mm)
<b>Drive</b>	7 / 17 rpm clockwise, 7 rpm counter-clockwise
Torque	880 Nm (650 ft-lbs.)
<b>Dimensions</b>	
Height	2135 mm (84 in.)
Width	1425 mm (56 in.)
Depth	1675 mm (66 in.)

Some dimensions, capacities and specifications may vary depending on tire and wheel configurations.



**TCX70-21UVE**

## Model

**TCX70-21UVE** 230V, 1ph, 50/60HZ

## Standard equipment

- ✓ Large 145mm metal cone (RP11-5-103627)
- ✓ Standard 120mm metal cone protectors (2 pieces) (RP11-4-103232A)
- ✓ Small 58mm cone (RP11-462414B)
- ✓ Small 74mm cone (RP11-4-118295A)
- ✓ Cone spacer (RP11-5-103627)
- ✓ Valve core remover (RP11-2020689)
- ✓ Bead starting tool (RP11-4-405496A)
- ✓ Bead-pressing clamp (MPR) (RP11-801262417)
- ✓ Wheel lift (RP11-8-11100415)
- ✓ Paste & brush

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

1118AH

Copyright © 2018, Hunter Engineering Company

## Optional equipment



### **Blast inflator** **RP11-8-11100416**

Directs large blast of compressed air exactly where needed to seat the bead.



### **Reverse rim flange kit** **RP11-8-11100039**

Ideal for plastic clad wheels or reverse wheels where maximum protection is needed.



### **Clamp adaptor** **RP11-8-11100417**

Adds clamping capability for truck wheels with large center holes. Adds clamping height for high offset wide wheels.

**HUNTER**  
**Engineering Company**

[www.hunter.com](http://www.hunter.com)

11250 Hunter Drive, Bridgeton, MO 63044, USA  
Tel: +1-314-731-3020, Fax: +1-314-731-0132  
Email: [international@hunter.com](mailto:international@hunter.com)

Form 7612-TE-05, 11/18