

# RX72, RX72-PS & RX72-IS

## Surface Mount Lift Rack

**HUNTER**  
Engineering Company

### SPECIFICATIONS



*RX72-IS Shown (jacks optional)*

#### Power Requirements (for available models)

**215E** 200/208/230 VAC, 1 phase, 50 or 60 HZ,  
26 Amp

**435E** 208/230/400/460 VAC, 3 phase, 50 HZ,  
18 Amp (208/230) / 9 Amp (400/460) draw

#### Site Specifications

**Air Supply Requirements** 6.2-10.3 bar (90-150 PSI)  
Jacks require 8.6 bar (125 PSI) for full capacity

**Minimum Concrete Spec.** 76 mm (3 in.) thick,  
20,700 kPa (3000 PSI) rating

**Maximum Floor Slope** 51 mm (2 in.) over 3200 mm (126 in.)

#### Product Specifications

**Max. Vehicle Weight** 7200 kg (16,000 lbs.)

#### Max. Wheelbase

**General Service** 4750 mm (187 in.)

**Two-Wheel Alignment** 4623 mm (182 in.)

**Four-Wheel Alignment** 4013 mm (158 in.)

**Alignment Height** All lock positions

**Min. Four-Wheel Alignment** 2235 mm (88 in.)

**Lifting Speed** 2-spd, 32 to 60 seconds (depends on load)


**Lowering Speed** 2-speed, 25 seconds

### MODEL FEATURES / DIMENSIONS / OPTIONS

Features	(std.)	-PS	-IS
2-Speed Lifting and Lowering	✓	✓	✓
<b>FIA</b> Fully Integrated Alignment		✓	✓
<b>POWER SLIDE</b>		✓	✓
<b>INFLATION STATION</b>			✓
9000-lb Swing Air Jacks	Available Option		

Dimension	
<b>Width (W1)</b>	2350 mm 92.5 in.
<b>Inside Width (W2)</b>	1016 mm 40 in.
<b>Length (L)</b>	6540 mm 257.5 in.
<b>Deck Length (DL)</b>	5283 mm 208 in.
<b>Runway Width (R)</b>	660 mm 26 in.
<b>Raised Height (H1)</b>	1930 mm (std) / 1727 mm (16k) 76 in.(std) / 68 in.(16k)
<b>Stack Height (H2)</b>	229 mm 9 in.

Options	Add. Length	Kit #
<b>Approach Ramp Ext. (Back)</b>	330 mm 13 in.	147-104-1 2 required
<b>Extended Approach Ramp Ext. (Back)</b>	457 mm 18 in.	147-113-1 2 required
<b>Conventional Sensor Ext. (Front)</b>	305 mm 12 in.	20-2497-1
<b>Drive-Thru Kit (Front)</b>	1346 mm 53 in.	20-2498-1
<b>Extended Drive-Thru Kit (Front)</b>	1549 mm 61 in.	20-2501-1



Continued on Page 2

For general inquiries visit:  
[www.hunter.com](http://www.hunter.com)


For local contact visit:  
[www.hunter.com/hunter-international](http://www.hunter.com/hunter-international)

# RX72, RX72-PS & RX72-IS

## Surface Mount Lift Rack

**HUNTER**  
Engineering Company

### SPECIFICATIONS



\*Non-standard positioning of control console is limited to a maximum space between console and rack of 1829 mm (6 feet) at the approach ramp end and 5182 mm (17 feet) at the turnplate end. Additional threshold and perhaps hydraulic hoses will be required (refer to Installation Instruction for details).