

HARDWARE / SPECIFICATIONS / FEATURES / ACCESSORIES



| Features | |
|----------------------------------|---|
| Power Requirements | 115/230V, 15 amp*, 50/60 Hz, 1 ph † |
| Monitor Class | 24", 27", or 32" Widescreen LCD (Optional) |
| Printer Drawer | Yes - Standard (Except WA520E and WA510E) |
| Console-top Storage and Charging | Yes - Standard (Large Cabinets Only) |
| Color Ink Jet Printer | Optional |
| Steering Wheel Holder | Yes - Standard |
| Brake Pedal Depressor | Yes - Standard |
| Wireless Remote | Standard / Optional on WA560E / 520E / 510E |
| Internet Connection | Ethernet cable recommended |
| | |

Features and supported sensors are dependent on the installed WinAlign® account. * Amperage shown is minimal circuit rating the provided of th

Continued on Reverse

For aligner information visit: www.hunter.com/alignment Because of continuing technological advancements, specifications, models and options are subject to change without notice.

For general inquiries visit: www.hunter.com

WinAlign[®] WA600 / WA500 Series Consoles



SENSOR COMMUNICATION and STORAGE COMPATIBILITY


| | DSP760T | DSP740T | DSP506T | HE421 | HS421 | HS401 | DSP600 | DSP700 | DSP500 |
|--|--------------------|---------|---------|--------------------|-------|-------|--------|--------|--------|
| WinAlign [®] Version Required* | V14.2 | V14.2 | V14.1 | V14.1 | V14.1 | V14.1 | V14.1 | V14.1 | V14.1 |
| Sensor Communications Support | Ø | Ø | Ø | S | Ø | Ø | Ø | Ø | Ø |
| Sensor Storage Support | Ø | Ø | | Ø | Ø | Ø | | Ø | |
| | Heavy Duty Sensors | | | Light Duty Sensors | | | | | |


CONSOLE CONFIGURATIONS

| | WA680E | WA670E | WA580E | WA570E | WA560E | WA520E | WA510E |
|---------------------------|---------------------------------|---------------------------------|-------------------------------|-------------------------------|-------------------------------|--------------------------|--------------------------|
| Large Cabinet | Ø | | Ø | | | | |
| Compact Cabinet | | Ø | | Ø | Ø | | |
| Column/Wall-mount | | | | | | Ø | |
| Economy Console | | | | | | | Ø |
| LCD (When Equipped) | 32 in. Widescreen | 27 in. Widescreen | 24 in. Widescreen | 24 in. Widescreen | 24 in. Widescreen | 24 in. Widescreen | 24 in. Widescreen |
| Width (W) | 1092 mm 43 in. | 813 mm 32 in. | 1092 mm 43 in. | 813 mm 32 in. | 813 mm 32 in. | 775 mm 30.5 in | 699 mm 27.5 in. |
| Open Width (W1) | 2019 mm 79.5 in. | - | 2019 mm 79.5 in. | - | - | - | - |
| Height (<mark>H</mark>) | 1778 - 1842 mm 70 - 72.5 in. | 1740 - 1803 mm 68.5 - 71 in. | 1651 - 1727 mm 65 - 68 in. | 1651 - 1727 mm 65 - 68 in. | 1651 - 1727 mm 65 - 68 in. | 1067 mm 42 in. | 1486 mm 58.5 in. |
| Depth (D) | 635 mm 25 in. | 635 mm 25 in. | 635 mm 25 in. | 635 mm 25 in. | 635 mm 25 in. | 597 mm 23.5 in | 597 mm 23.5 in |
| Shipping Weight | 245 kg 541 lbs. | 192 kg 424 lbs. | 226 kg 498 lbs. | 178 kg 394 lbs. | 176 kg 388 lbs. | 107 kg 236 lbs. | 81 kg 178 lbs. |


Space consideration for storage of accessories and targets: For large and compact consoles, add 254 mm (10 inches) to depth for accessories. Optional rear storage will require at least 406 mm (16 inches) behind console.


If mounting two DSP700T sensors and mini adaptors, add 813 mm (32 inches) to width and 254 mm (10 inches) to depth (front). If mounting four DSP700T sensors and adaptors, add 813 mm (32 inches) to width, 254 mm (10 inches) to depth (front) and 305 mm (12 inches) to depth (rear).






Compact Console





Column / Wall Console



For aligner information visit: www.hunter.com/alignment

For general inquiries visit: www.hunter.com Because of continuing technological advancements, specifications, models and options are subject to change without notice.

Copyright © 2017, Hunter Engineering Company Form 7403-TE, 07-17