

# ***TCX45 Tire Changer***

***Easy-to-use conventional tire changer***



# Specifications

## Electrical

|        |                 |
|--------|-----------------|
| -1-1-6 | 110V, 1ph, 60Hz |
| -2-1-6 | 220V, 1ph, 60Hz |
| -2-1-5 | 220V, 1ph, 50Hz |

## Wheel clamping

|                    |             |
|--------------------|-------------|
| External (min-max) | 11 - 22 in. |
| Internal (min-max) | 13 - 25 in. |

|                              |        |
|------------------------------|--------|
| <b>Maximum tire diameter</b> | 980 mm |
|------------------------------|--------|

|                          |        |
|--------------------------|--------|
| <b>Maximum rim width</b> | 12 in. |
|--------------------------|--------|

|                            |        |
|----------------------------|--------|
| <b>Bead loosener width</b> | 320 mm |
|----------------------------|--------|

|                             |         |
|-----------------------------|---------|
| <b>Table rotation speed</b> | 8.5 rpm |
|-----------------------------|---------|

|                    |       |
|--------------------|-------|
| <b>Noise level</b> | 70 dB |
|--------------------|-------|

|                           |            |
|---------------------------|------------|
| <b>Operation pressure</b> | 8 - 10 bar |
|---------------------------|------------|

|                       |        |
|-----------------------|--------|
| <b>Machine weight</b> | 208 kg |
|-----------------------|--------|

## Dimensions

|        |         |
|--------|---------|
| Height | 1940 mm |
| Width  | 1115 mm |
| Depth  | 960 mm  |

Some dimensions, capacities and specifications may vary depending on tire and wheel configurations.

## Models

**TCX45** Swing arm tire changer

**TCX45GP** Swing arm tire changer with tubeless inflation

Add:

**-1-1-6** For 110V, 1ph, 60Hz

**-2-1-6** For 220V, 1ph, 60Hz

**-2-1-5** For 220V, 1ph, 50Hz

## Standard equipment

- ✓ Inflation hose and gauge
- ✓ Tire lever
- ✓ Spare mount head protectors
- ✓ Double-acting shovel cylinder

## Optional equipment

**RP11-8-11120032** Bead press arm upgrade

**RP11-8-11100044** Plastic jaw protectors

**RP11-801258383** Side shovel protectors (6)

**RP11-8-11400098** Bead lever protectors (4)



**TCX45GP** with optional bead press arm

**TCX45**



Be sure to check out other Hunter literature for more quality products from Hunter Engineering.

**HUNTER**  
Engineering Company

[www.hunter.com](http://www.hunter.com)

11250 Hunter Drive, Bridgeton, MO 63044, USA

Tel: 1-314-731-3020, Fax: 1-314-731-0132

Email: [international@hunter.com](mailto:international@hunter.com)

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

0917BH

Copyright © 2017, Hunter Engineering Company

Form 7084-TE-05, 09/17  
Supersedes form 7084-TE-05, 12/15