



# Unmanned Inspection Ordering Guide

P  
R  
N  
2

How to choose a **Quick Check DRIVE** supergroup

**1 Sensors**

✓ **QCD**

**DRV1** Quick Check Drive® alignment sensors



**Supergroups include:**  
**BDC** Damage-Cam with standard 90-day storage\*



**2 Console**

✓ **92**

**WU592** wall-mounted Quick Check Drive® console



RECOMMENDED

**3 Tire Tread**

✓ **TF**

**QTEF** Quick Tread Edge® flush-mounted sensors



RECOMMENDED

**4 Enhanced Vehicle ID**

✓ **ECS**

**20-3584-1** External vehicle identification camera\*\* (short focal length)



**QCD92TFECS**

# How to choose a **Quick Tread EDGE** supergroup

**1 Sensors**

✓ **QTE**

**QTE** Quick Tread Edge® sensors



**2 Console**

✓ **92**

**WU592** wall-mounted Quick Tread Edge® console



RECOMMENDED

**3 Flush-Mounting**

□ **F**

**QTEF** Quick Tread Edge® flush-mounted sensors



**4 Quick ID™**

✓ **IDS**

**QIDS** Quick ID™ vehicle identification system (short focal length)



**QTE92IDS**



Equipment also available in black (add **BLK** to part#)  
QTE ramps available only in black



**Automatic results display with Flightboard™**

Results shown dependent on selected equipment.

Display sourced locally.

Refer to **7614-T** for more information.

\* Requires active HunterNet® subscription (3-years included)

\*\* Recommended in all locales for best performance on new/redesigned license plates. Refer to **7563-T** for more details

# ... or build your own system



## Console

<b>WU592</b>	Wall-mounted Quick Check Drive® console <b>20-3356-1BLK</b> Optional pedestal for WU592
<b>WU572</b>	Mobile Quick Check Drive® console



## Body Image Capture

<b>BDC</b>	3-year subscription with 90-day image storage <i>Requires active HunterNet® subscription</i>
------------	---

## Alignment Sensors

<b>DRV1</b>	Quick Check Drive® alignment sensors
-------------	--------------------------------------



## Tire Tread

<b>QTEF</b>	Flush-mounted Quick Tread Edge® sensors
<b>QTE</b>	Surface-mounted Quick Tread Edge® sensors <i>Not compatible with Quick Check Drive®</i>

## Vehicle Identification



<b>20-3584-1</b>	Short focal length camera for Quick Check Drive® <i>For plate-to-camera distance of 96-180 in. Best for systems installed near service drive entrance</i>
<b>20-3541-1</b>	Long focal length camera for Quick Check Drive® <i>For plate-to-camera distance of greater than 180 in. Used with systems installed in the middle of service drive</i>
<b>QIDS</b>	Short focal length camera for Quick Tread Edge® <i>For plate-to-camera distance of 96-180 in. Best for systems installed near service drive entrance</i>
<b>QID</b>	Long focal length camera for Quick Tread Edge® <i>For plate-to-camera distance of greater than 180 in. Used with systems installed in the middle of service drive</i>

Refer to **QT07846-00** when choosing long or short focal length cameras.



**QCD92TF** – shown with optional 20-3356-1BLK pedestals



**QTE92**



Equipment also available in black (add **BLK** to part#)  
QTE ramps available only in black

Quick Check, Quick Check Drive, Quick Tread Edge, and HunterNet are registered trademarks of Hunter Engineering company.

0821HH

Copyright © 2021, Hunter Engineering Company

**HUNTER**  
Engineering Company

[www.hunter.com](http://www.hunter.com)

Form QB07552-00, 08/21  
Supersedes Form QB07552-00, 12/20